

JREZ LLC

JREZ ® 13U PRODUCT DATA SHEET

POLYESTER RESIN

FEATURES: JREZ 13U is a saturated polyester premium grease vehicle. Depending on formulating techniques, lubricity can be retained at temperatures ranging from -100 F to 400 F.

DESCRIPTION: JREZ13U is a low molecular weight product so that thixotropic additives are recommended in order to retain lubrication qualities at high shear. This product is 100% polymeric polyester with no additives so that the lubricant formulator has maximum flexibility.

PHYSICAL CHARACTERISTICS:

Percent Active	100
Solvent System	None
Acid No.	5 max.
Viscosity (Gardner)	P-Y
Weight per Gallon	9.5 pounds
Tg deg C	60
Appearance	Oily Liquid

PACKAGING: 55-gallon drums. Contact us for additional package options.

HEALTH, SAFETY AND ENVIRONMENTAL: Please refer to Safety Data Sheet.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without warranty as conditions and methods of use are in the control of others. We recommend that prospective users determine the suitability of materials and suggestions before adopting same on a commercial scale. Suggestions for product application should not be understood as recommendations that they be implemented in violation of any patent. Data shown are typical and are subject to change. The user is responsible for handling this product or wastes containing this product in a safe manner and in compliance with all pertinent regulations.



JREZ LLC

233 Old Short Hills Road
Short Hills, NJ 07078

PHONE (973) 738-6194

WEB SITE <http://www.jrezllc.com>