

# JREZ LLC

## JREZ ® 17-2 PRODUCT DATA SHEET

### THERMOPLASTIC ACRYLIC RESIN SOLUTION

**FEATURES:** JREZ 17-2 is an adhesion promoted polymer with medium hardness and good flexibility. It is suitable for air dry as well as baking. It has excellent adhesion to raw and primed metals, including aluminum, copper, bronze, steel and zinc. It also has adhesion to glass. JREZ 17-2 has good compatibility with pigments as well as most monomeric plasticizers, some polymeric plasticizers and vinyl resins. It is not recommended for alkyd systems. JREZ 17-2 is suitable as a size coating for hot stamping foils and as a tie coat on aluminum roofing.

**DESCRIPTION:** JREZ 17-2 is available in other solvents and at different viscosities. Please contact us for your specific requirements.

#### **PHYSICAL CHARACTERISTICS:**

Percent Non-Volatiles	50
Solvent System	Toluene
Viscosity (approx.; cps)	10,000
Weight per Gallon	8.1 Pounds
Tg deg C	60
Color	Gardner 1 Max

**PACKAGING:** 55-gallon drums, Bulk. Contact us for additional package options.

**HEALTH, SAFETY AND ENVIRONMENTAL:** Please refer to Safety Data Sheet.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without warranty as conditions and methods of use are in the control of others. We recommend that prospective users determine the suitability of materials and suggestions before adopting same on a commercial scale. Suggestions for product application should not be understood as recommendations that they be implemented in violation of any patent. Data shown are typical and are subject to change. The user is responsible for handling this product or wastes containing this product in a safe manner and in compliance with all pertinent regulations.



JREZ LLC

233 Old Short Hills Road  
Short Hills, NJ 07078

PHONE (973) 738-6194

WEB SITE <http://www.jrezllc.com>